

# NEW PLYMOUTH STEEL SUPPLIES LTD

CHE	CK VALVES	
15mm  20mm  25mm  32mm    40mm  50mm	ENDS: Screwed BSP. BODY & TRIM: Brass body and trim, NBR seal, stainless steel spring. RATING: Upto 20 bar CWP20°C to +100°C. APPLICATIONS: Pneumatic & water systems, air conditioning and heating systems. With strainer – a foot valve for irrigation, industrial water supply, water circulation.	Mondial Check Valve
8mm  10mm  15mm  20mm    10 PCS BOX  10 PCS BOX  6 PCS BOX  6 PCS BOX  6 PCS BOX    25mm  32mm  40mm  50mm    6 PCS BOX  4 PCS BOX  2 PCS BOX    6 PCS BOX  4 PCS BOX  2 PCS BOX    1 PCS BOX  1 PCS BOX  1 PCS BOX    1 PCS BOX  1 PCS BOX  1 PCS BOX	ENDS: Screwed BSP. BODY & TRIM: Brass body, polysultone jumper, nylon 30% glass filler jumper guide, NBR seal, stainless steel spring. RATING: From 40 bar CWP for 10mm to 10 bar for 100mm30°C to +110°C. APPLICATIONS: Pneumatic & water systems, air conditioning and heating systems. With strainer – a foot valve for irrigation, industrial water supply, water circulation.	Bonomi Valstop Spring Check Valve
15mm  20mm  25mm  32mm    40mm  50mm  65mm  80mm    100mm  50mm  50mm  50mm    Code: BVVS  50mm  50mm  50mm	ENDS: Screwed BSP. BODY & TRIM: Stainless steel basket. RATING: APPLICATIONS: Used with Valstop, Mondial & Europa Check Valves.	Bonomi Valstop Strainer
10mm  15mm  20mm  25mm    32mm  40mm  50mm	ENDS: Screwed BSP. BODY & TRIM: Polymer Plastic. RATING: APPLICATIONS: Used with Valstop, Mondial & Europa Check Valves.	ITAP Polymer Strainer
10mm  15mm  20mm  25mm    10 PCS BOX  10 PCS BOX  8 PCS BOX  6 PCS BOX    32mm  40mm  50mm  65mm    4 PCS BOX  4 PCS BOX  2 PCS BOX  1 PCE BOX    1 PCE BOX  1 PCE BOX  2 PCS BOX  1 PCE BOX    1 PCE BOX  1 PCE BOX  1 PCE BOX  1 PCE BOX	ENDS: Screwed BSP. BODY & TRIM: Brass body, stainless steel plate, NBR seal, stainless steel spring. RATING: Upto 18 bar CWP30°C to +110°C. APPLICATIONS: Pneumatic & water systems, air conditioning and heating systems. With strainer – a foot valve for irrigation, industrial water supply, water circulation.	Europa Check Valve

1



## NEW PLYMOUTH STEEL SUPPLIES LTD

### CHECK VALVES

15mm 20mm 25mm 32mm	ENDS: Screwed BSP.	Bonomi Clapet Swing Check Valve with Soft Seat		
20 PCS BOX 15 PCS BOX 10 PCS BOX 6 PCS BOX 40mm 50mm	BODY & TRIM: Forged brass body and flap with NBR rubber seat.			
4 PCS BOX 2 PCS BOX	RATING: From 12 bar CWP for 15mm to 10 bar for 50mm.	. <u>6</u> −23		
Code: BVCS	APPLICATIONS: Water, liquids and gases.			
15mm 20mm 25mm 32mm ENDS: Bonomi Clapet Swing Check				
20 PCS BOX 15 PCS BOX 10 PCS BOX 6 PCS BOX	Screwed BSP.	Valve with Metal Seat		
40mm 50mm	BODY & TRIM: Forged brass body and flap with metal seat.			
4 PCS BOX 2 PCS BOX	RATING: From 12 bar CWP for 15mm to 10 bar for 50mm.	6.63		
Code: BVCSM	APPLICATIONS: Water, liquids and gases.			
15mm 20mm 25mm 32mm	ENDS: Screwed BSP.	Liquetec LVC49 Swing Check Valve		
40mm 50mm 65mm 80mm	BODY & TRIM: LG2 cast gunmetal.			
	RATING:			
EXISTING STOCK	13.8 bar CWP. Temperature 180°C. APPLICATIONS:			
Code: LVC49	Hot and cold water, oil, etc.			
80mm 100mm 150mm 200mm	ENDS: Grooved.	Shurjoint 453 UG Dual Plate Check Valve		
	BODY & TRIM:			
	Ductile iron body, bronze plates. RATING:	and the second second		
	14 bar CWP.	and the second sec		
Code: SCV	UL listed & FM approved.			
65mm 80mm 100mm 150mm		Fivalco		
	ENDS: Grooved.	1 touto		
200mm	BODY & TRIM: Ductile iron body, seat ring S/S. EPDM faced clapper.	The Wilder		
L	RATING: 21 bar CWP.	A ACTION		
Code: FCV	UL listed & FM approved.			

-----



## NEW PLYMOUTH STEEL SUPPLIES LTD

#### CHECK VALVES

50mm  65mm  80mm  100mm    150mm  200mm	ENDS: Wafer to suit ANSI 150 flanges. BODY & TRIM: 316 S/S body, plates and spring. Viton seat. RATING: Pressure to ANSI 150. Temp. 150°C. APPLICATIONS: Chemical services, liquids and gases, steam.	Astam Stainless Steel Check Value
50mm65mm80mm100mm125mm150mm200mm250mm300mm500mm500mm500mmCode: ACVCIEPDM Seat500mmCode: ACVBBUNA (NBR) Seat500mm	ENDS: Wafer for T/E, ANSI 150, PN16. BODY & TRIM: CI body, stainless steel discs, EPDM or BUNA seat. RATING: 16 bar CWP. Complete with rubber flange gaskets.	Maxiflo Check Valve Dual Discs
15mm  20mm  25mm  32mm    40mm  50mm	ENDS: Screwed BSP. BODY & TRIM: LG2 bronze body, S/S disc and seat. RATING: 27.5 bar CWP. Temperature 260°C. APPLICATIONS: Steam, gases.	Liquetec LVC45 Lift Check Valve
15mm  20mm  25mm  32mm    40mm  50mm	ENDS: Screwed NPT or socket weld. BODY & TRIM: Carbon steel body, 13% chrome S/S trim, full port. RATING: Class 800. 136 bar. APPLICATIONS: Petrochemical and power plants, general steam use.	DK Piston Check Valve
15mm  20mm  25mm  32mm    40mm  50mm	ENDS: Screwed BSP. BODY & TRIM: 316 S/S. RATING: 200 psi CWP, up to 230°C. APPLICATIONS: Chemicals, food, corrosive environments.	HSY 790 5/5 Swing Check Value

-----