

NEW PLYMOUTH STEEL SUPPLIES LTD

GLOBE VALVES

8mm	10mm	15mm	20mm
25mm	40mm	50mm	

Code: LVS16


ENDS:
Screwed BSP.

BODY & TRIM:
Bronze with integral seat and renewable composition disc.

RATING:
27 bar CWP. 13.6 bar steam.
Temperatures to 230°C.

APPLICATIONS:
Medium and low pressure steam services, also water supply, compressed air, oil and petrol.

Liquetec LVS16 Globe Valve



8mm	10mm	15mm	20mm
25mm	32mm	40mm	50mm

Code: LVS11


ENDS:
Screwed BSP.

BODY & TRIM:
Bronze, with union bonnet, and with stainless steel seat and disc.

RATING:
41 bar CWP. 20 bar steam. Temperatures to 260°C.

APPLICATIONS:
Medium pressure boiler and steam services, also cold services.

Liquetec LVS11 Globe Valve



15mm	20mm	25mm	32mm
40mm	50mm		

Code: LVS12


ENDS:
Flanged DIN PN16 (undrilled).

BODY & TRIM:
Bronze, with union bonnet, and with bronze seat and disc.

RATING:
15.5 bar CWP. 10 bar steam.
Temperatures to 260°C.

APPLICATIONS:
Medium pressure boiler and steam services, also cold services.

Liquetec LVS12 Globe Valve



NEW PLYMOUTH STEEL SUPPLIES LTD

GLOBE VALVES

<table border="1"> <tr> <th>15mm</th> <th>20mm</th> <th>25mm</th> <th>32mm</th> </tr> <tr> <td> </td> <td> </td> <td> </td> <td> </td> </tr> <tr> <th>40mm</th> <th>50mm</th> <td> </td> <td> </td> </tr> <tr> <td> </td> <td> </td> <td> </td> <td> </td> </tr> </table> <p>Code: HSGLVSS</p>	15mm	20mm	25mm	32mm					40mm	50mm							<p>ENDS: Screwed BSP.</p> <p>BODY & TRIM: ASTM CF8M 316 S/S body, bonnet, spindle and seats.</p> <p>RATING: 200 psi – 14 bar CWP.</p> <p>APPLICATIONS: Corrosive fluids/gases. Food, drug, chemical process.</p>	<p><i>HSY Fig. GB-200 S/S Globe Valve</i></p> 
15mm	20mm	25mm	32mm															
40mm	50mm																	
<table border="1"> <tr> <th>15mm</th> <th>20mm</th> <th>25mm</th> <th>32mm</th> </tr> <tr> <td> </td> <td> </td> <td> </td> <td> </td> </tr> <tr> <th>40mm</th> <th>50mm</th> <td> </td> <td> </td> </tr> <tr> <td> </td> <td> </td> <td> </td> <td> </td> </tr> </table> <p>EXISTING STOCK ONLY</p> <p>Code: BFVGL</p>	15mm	20mm	25mm	32mm					40mm	50mm							<p>ENDS: Screwed NPT or socket weld.</p> <p>BODY & TRIM: Carbon steel body, 13% chrome S/S trim. Bolted bonnet.</p> <p>RATING: Class 800 138 bar (2000 psi) CWP. 55 bar (800 psi) at 450°C.</p> <p>APPLICATIONS: Petrochemical and power plants, general steam use.</p>	<p><i>Bonney Forge Globe Valve</i></p> 
15mm	20mm	25mm	32mm															
40mm	50mm																	
<table border="1"> <tr> <th>15mm</th> <th>20mm</th> <th>25mm</th> <th>32mm</th> </tr> <tr> <td> </td> <td> </td> <td> </td> <td> </td> </tr> <tr> <th>40mm</th> <th>50mm</th> <td> </td> <td> </td> </tr> <tr> <td> </td> <td> </td> <td> </td> <td> </td> </tr> </table> <p>Code: DKVGLSW</p>	15mm	20mm	25mm	32mm					40mm	50mm							<p>ENDS: Socket weld.</p> <p>BODY & TRIM: Carbon steel body, 13% chrome S/S trim. Bolted bonnet.</p> <p>RATING: Class 800 136 bar.</p> <p>APPLICATIONS: Petrochemical and power plants, general steam use.</p>	<p><i>DK Globe Valve</i></p> 
15mm	20mm	25mm	32mm															
40mm	50mm																	
<table border="1"> <tr> <th>8mm</th> <th>10mm</th> <th>15mm</th> </tr> <tr> <td> </td> <td> </td> <td> </td> </tr> </table> <p>Code: VMNV</p>	8mm	10mm	15mm				<p>ENDS: Screwed BSPT.</p> <p>BODY & TRIM: 316SS, PTFE Packing.</p> <p>RATING: 6000 PSI, 413 Bar.</p>	<p><i>VM Needle Valve ND6000</i></p> 										
8mm	10mm	15mm																