






NEW PLYMOUTH STEEL SUPPLIES LTD

MISCELLANEOUS VALVES

<table border="1"> <thead> <tr> <th>15mm</th> <th>20mm</th> </tr> </thead> <tbody> <tr> <td> </td> <td> </td> </tr> </tbody> </table> <p>Code: BVPR361</p>	15mm	20mm			<p>ENDS: Screwed BSP.</p> <p>BODY & TRIM: Brass body, S/S seat, NBR seal.</p> <p>RATING: Inlet pressure up to 15 bar. Outlet pressure 0.5 to 4 bar. Temperature to 80°C.</p>	<p><i>Itap 361 Pressure Reducing Valve</i></p> 				
15mm	20mm									
<table border="1"> <thead> <tr> <th>32mm</th> <th>40mm</th> <th>50mm</th> <th>65mm</th> </tr> </thead> <tbody> <tr> <td> </td> <td> </td> <td> </td> <td> </td> </tr> </tbody> </table> <p>ALSO AVAILABLE TO ORDER WITH IP65 RATED SWITCH BOX – CODE VVMIP65</p> <p>Code: VVM</p>	32mm	40mm	50mm	65mm					<p>ENDS: Screwed BSP.</p> <p>BODY & TRIM: Brass nickel plated full bore ball valve rated to 25 bar. Monitored valve for fire sprinkler systems. Complete with tamper proof switch box. Insurance Council listed Certificate No. 461.</p>	<p><i>Vitech 12-9 Fire Sprinkler Ball Valve</i></p> 
32mm	40mm	50mm	65mm							
<table border="1"> <thead> <tr> <th>65mm</th> </tr> </thead> <tbody> <tr> <td> </td> </tr> </tbody> </table> <p>Code: MVFH</p>	65mm		<p>ENDS: Screwed BSP.</p> <p>BODY & TRIM: Brass nickel plated full bore valve.</p> <p>Fire hydrant riser and outlet valve. Lockable ratchet lever handle.</p> <p>Insurance Council listed. Certificate No. 462.</p>	<p><i>Maxiflo Landing Valve</i></p> 						
65mm										
<table border="1"> <thead> <tr> <th>65mm</th> </tr> </thead> <tbody> <tr> <td> </td> </tr> </tbody> </table> <p>Code: MVBCS</p>	65mm		<p>ENDS: Screwed BSP.</p> <p>BODY & TRIM: Brass.</p> <p>RATING: 200 psi, 14 bar.</p>	<p><i>Maxiflo Swing Check Valve</i></p> 						
65mm										
<table border="1"> <thead> <tr> <th>15mm</th> <th>20mm</th> <th>25mm</th> </tr> </thead> <tbody> <tr> <td> </td> <td> </td> <td> </td> </tr> </tbody> </table> <p>Code: ABVX</p>	15mm	20mm	25mm				<p>ENDS: BSP Taper F/F.</p> <p>BODY & TRIM: Nickel plated brass body, full bore chrome plated brass ball PTFE seats.</p> <p>RATING: CWP – 20 bar. Max temp 150°C.</p> <p>APPLICATIONS: For insulated pipelines.</p>	<p><i>Asmuss Xstemball Valve</i></p> 		
15mm	20mm	25mm								