

NEW PLYMOUTH STEEL SUPPLIES LTD

BALL VALVES

8mm	10mm	15mm	20mm
25 PCS BOX	25 PCS BOX	15 PCS BOX	12 PCS BOX
25mm	32mm	40mm	50mm
12 PCS BOX	4 PCS BOX	4 PCS BOX	2 PCS BOX
65mm	80mm	100mm	
1 PCS BOX	1 PCS BOX	1 PCS BOX	

Code: BVS214

ENDS:
BSP F/F.

BODY & TRIM:
Nickel plated brass body, full bore
chrome plated brass ball PTFE seats.

RATING:
CWP - 50 bar size 8mm to 10 bar size
100mm. Max temp 150°C.

APPLICATIONS:
Hot and cold water, compressed air, oils,
non-aggressive chemicals, etc.

Bonomi Basic Ball Valve



15mm	20mm	25mm
PCS BOX	PCS BOX	PCS BOX
32mm	40mm	50mm
PCS BOX	PCS BOX	PCS BOX

Code: BVS218

T-HANDLE SIZES 15, 20, 25

Code: BVS215

LEVER HANDLE


ENDS:
BSP M/F.

BODY & TRIM:
Nickel plated brass body, full bore
chrome plated brass ball PTFE seats.

RATING:
CWP - 40 bar size 15mm to 20 bar size
50mm. Max temp 150°C.

APPLICATIONS:
Hot and cold water, compressed air, oils,
non-aggressive chemicals, etc.

Bonomi Basic Ball Valve



8mm	10mm	15mm	20mm
30 PCS BOX	28 PCS BOX	20 PCS BOX	12 PCS BOX
25mm			
9 PCS BOX			

Code: BVS217


ENDS:
BSP F/F.

BODY & TRIM:
Nickel plated brass body, full bore
chrome plated brass ball PTFE seats.

RATING:
CWP - 50 bar size 8mm to 30 bar size
25mm. Max temp 150°C.

APPLICATIONS:
Hot and cold water, compressed air, oils,
non-aggressive chemicals, etc.

Bonomi Basic Ball Valve



6mm	8mm	10mm	15mm
24 PCS BOX	24 PCS BOX	24 PCS BOX	24 PCS BOX

"NEW STYLE"

Code: BVM330	F/F LEVER
Code: BVM331	M/F LEVER
Code: BVM333	F/F SCREW


ENDS:
Screwed BSP F/F or M/F.

BODY & TRIM:
Nickel plated, reduced bore, brass
body. Chrome plated brass ball, PTFE
seats, NBR o-ring gland seal. Handle or
screwdriver operation.

RATING:
10 bar (150 psi) CWP. 90°C max.

APPLICATIONS:
A light, compact valve of neat
appearance. Suitable for water,
compressed air, etc.

Bonomi Microball Valve



NEW PLYMOUTH STEEL SUPPLIES LTD

BALL VALVES

8mm	10mm	15mm	20mm
20 PCS BOX	20 PCS BOX	20 PCS BOX	12 PCS BOX
25mm	32mm	40mm	50mm
8 PCS BOX	4 PCS BOX	4 PCS BOX	2 PCS BOX
1 PCS BOX	1 PCS BOX		

Code: BVT201

ENDS:
BSP TAPER F/F.

BODY & TRIM:
Nickel plated brass body, full bore chrome plated brass ball PTFE seats.

RATING:
CWP - 50 bar size 8mm to 12 bar size 100mm. Max temp 150°C.

APPLICATIONS:
Hot and cold water, compressed air, oils, non-aggressive chemicals, natural gas.



Bonomi Topic Ball Valve

8mm	10mm	15mm	20mm
30 PCS BOX	30 PCS BOX	30 PCS BOX	12 PCS BOX
25mm	32mm	40mm	50mm
9 PCS BOX			


Code: BVT208 T-HANDLE 8mm - 25mm
Code: BVT202 LEVER HANDLE 15mm - 50mm

ENDS:
BSP TAPER M/F.

BODY & TRIM:
Nickel plated brass body, full bore chrome plated brass ball PTFE seats.

RATING:
CWP - 45 bar size 15mm to 20 bar size 50mm. Max temp 150°C.

APPLICATIONS:
Hot and cold water, compressed air, oils, non-aggressive chemicals, natural gas.



Bonomi Topic Ball Valve

8mm	10mm	15mm	20mm
30 PCS BOX	20 PCS BOX	25 PCS BOX	12 PCS BOX
25mm			
9 PCS BOX			


Code: BVT207

ENDS:
BSP TAPER F/F.

BODY & TRIM:
Nickel plated brass body, full bore chrome plated brass ball PTFE seats.

RATING:
CWP - 50 bar size 8mm to 35 bar size 25mm. Max temp 150°C.

APPLICATIONS:
Hot and cold water, compressed air, oils, non-aggressive chemicals, natural gas.



Bonomi Topic Ball Valve

15mm	20mm	25mm	32mm
20 PCS BOX	12 PCS BOX	8 PCS BOX	4 PCS BOX
40mm	50mm		
4 PCS BOX		2 PCS BOX	


Code: BVT221

ENDS:
BSP TAPER F/F.

BODY & TRIM:
Nickel plated brass body, full bore chrome plated brass ball PTFE seats.

RATING:
CWP - 50 bar size 8mm to 12 bar size 100mm. Max temp 150°C.

APPLICATIONS:
Hot and cold water, compressed air, oils, non-aggressive chemicals. Natural gas.



Bonomi Topgas Ball Valve with Yellow Handle

15mm	20mm	25mm	32mm
20 PCS BOX	12 PCS BOX	8 PCS BOX	4 PCS BOX
40mm	50mm		
4 PCS BOX		2 PCS BOX	


Code: BVTLH

ENDS:
BSP TAPER F/F.

BODY & TRIM:
Nickel plated brass body, full bore chrome plated brass ball PTFE seats.

RATING:
CWP - 50 bar size 8mm to 12 bar size 100mm. Max temp 150°C.

Lockable handle in both closed and open positions.



Bonomi Topic Ball Valve with Lockable Handle

NEW PLYMOUTH STEEL SUPPLIES LTD

MAXIFLO BALL VALVES

8mm	10mm	15mm	20mm
25mm	32mm	40mm	50mm
65mm	80mm	100mm	

Code: MVBB


ENDS:
BSP F/F.

BODY & TRIM:
Nickel plated brass body, full bore chrome plated brass ball PTFE seats, lever handle.

RATING:
CWP – 50 bar size 8mm to 17 bar size 100mm. Max temp 150°C.

APPLICATIONS:
Hot and cold water, air, oils, non-aggressive chemicals.

*Maxiflo Brass Ball Valve
General Purpose*



8mm	10mm	15mm	20mm
25mm	32mm	40mm	50mm
65mm	80mm	100mm	

Code: MVGAS

Code: MVGAST T Handle 8mm to 25mm


ENDS:
BSP TAPER F/F.

BODY & TRIM:
Nickel plated brass body, full bore chrome plated brass ball PTFE seats, lever and tee handle.

RATING:
CWP – 50 bar size 8mm to 17 bar size 100mm. Max temp 150°C.

APPLICATIONS:
Hot and cold water, compressed air, oils, non-aggressive chemicals, natural gas. AGA approval 6017.

*Maxiflo Brass Ball Valve
Gas Approved*



8mm	10mm	15mm	20mm
25mm	32mm	40mm	50mm

Code: MVGASMF

Code: MVGASMFT 8mm to 25mm

ENDS:
BSP TAPER M/F.

BODY & TRIM:
Nickel plated brass body, full bore chrome plated brass ball PTFE seats, lever and tee handle.

RATING:
CWP – 50 bar size 8mm to 25 bar size 50mm. Max temp 150°C.

APPLICATIONS:
Hot and cold water, compressed air, oils, non-aggressive chemicals, natural gas. AGA approval 6017.

*Maxiflo Brass Ball Valve
Gas Approved*



15mm	20mm	25mm	32mm
40mm	50mm		

Code: MVBBD

ENDS:
BSP.

BODY & TRIM:
DZR body and ball stem, full bore PTFE seats, lever handle.

RATING:
CWP – 25 bar. Max temp 150°C.

APPLICATIONS:
Potable water.
Watermark Spec 012.
Licence no. W653.
AGA approval 6017.

*Maxiflo DZR Brass Ball Valve
Gas Approved*



15mm	20mm	25mm	32mm
40mm	50mm		

Code: MVGASLH

ENDS:
BSP TAPER M/F.

BODY & TRIM:
Nickel plated brass body, full bore chrome plated brass ball PTFE seats, lockable handle.

RATING:
CWP – 50 bar size 8mm to 17 bar size 100mm. Max temp 150°C.

APPLICATIONS:
Hot and cold water, compressed air, oils, non-aggressive chemicals, natural gas. AGA approval 6017.

*Lockable Handle Maxiflo
Ball Valve*



NEW PLYMOUTH STEEL SUPPLIES LTD

VALVES

15mm				
Code: BVBIBO	WITH BLUE BUTTON OR RED BUTTON			


ENDS:
Screwed BSP.

BODY & TRIM:
Nickel plated brass body, chrome plated brass ball, PTFE seats, o-ring stem seals.

RATING:
16 bar CWP. Temp to 90°C.

APPLICATIONS:
Washing machine connections.

Bonomi Bibo Bib Cock



15mm	20mm	25mm	32mm	
40mm	50mm			
Code: BVTT				


ENDS:
Screwed BSP.

BODY & TRIM:
Nickel plated brass body, chrome plated brass ball, 4 PTFE seats and seals, special multi-position handle.

RATING:
16 bar CWP. 150°C max.

APPLICATIONS:
Hot and cold water, compressed air, oils, gases, fuels, non-aggressive chemicals.

Bonomi Trio 3-Way Ball Valve T-Port



8mm	10mm	15mm	20mm	
25mm	32mm	40mm	50mm	
Code: BVTL				


ENDS:
Screwed BSP.

BODY & TRIM:
Nickel plated brass body, chrome plated brass ball, PTFE seats and seals.

RATING:
10 bar CWP (150 psi). Temp 150°C max.

APPLICATIONS:
Hot and cold water, compressed air, oils, gases, fuels, non-aggressive chemicals.

Bonomi Duo 3-Way Ball Valve L-Port



15mm	20mm	25mm	32mm	
40mm	50mm			
Code: BVT 128				


ENDS:
Screwed BSP.

BODY & TRIM:
Nickel plated brass body, chrome plated brass ball, PTFE seats and seals.

RATING:
16 bar CWP. 150°C max.

APPLICATIONS:
Hot and cold water, compressed air, oils.

ITAP 3-Way Ball Valve T-Port



15mm	20mm	25mm	32mm	
40mm	50mm			
Code: BVL 128				


ENDS:
Screwed BSP.

BODY & TRIM:
Nickel plated brass body, chrome plated brass ball, PTFE seats and seals.

RATING:
16 bar CWP. 150°C max.

APPLICATIONS:
Hot and cold water, compressed air, oils.

ITAP 3-Way Ball Valve L-Port



NEW PLYMOUTH STEEL SUPPLIES LTD

BALL VALVES

<table border="1"> <thead> <tr> <th>15mm</th> <th>20mm</th> <th>25mm</th> <th>32mm</th> </tr> </thead> <tbody> <tr> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <th>40mm</th> <th>50mm</th> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	15mm	20mm	25mm	32mm					40mm	50mm							<p>ENDS: Screwed BSP F/F.</p> <p>BODY & TRIM: Body brass, full bore. Ball valve, PTFE seats, check valve nylon jumper, NBR seal, S/S spring.</p> <p>RATING: From 40 bar CWP for 15mm to 25 bar, 40mm. Temp. 100°C.</p> <p>APPLICATIONS: Water supply systems, HVAC, backflow prevention and test.</p>	<p><i>Robex-VT Triple Valve Combination Ball, Check, Test & Drain Valve</i></p> 
15mm	20mm	25mm	32mm															
40mm	50mm																	
<table border="1"> <thead> <tr> <th>15mm</th> <th>20mm</th> <th>25mm</th> </tr> </thead> <tbody> <tr> <td></td> <td></td> <td></td> </tr> </tbody> </table>	15mm	20mm	25mm				<p>ENDS: Screwed BSP, F/F.</p> <p>BODY & TRIM: Dezincification resistant copper alloy metals; PTFE seats.</p> <p>RATING: From 45 bar CWP for 15mm to 25 bar for 50mm. Temperatures to 150°C.</p> <p>APPLICATIONS: Services where chlorinated water or aggressive natural water causes zinc leaching in standard brass alloys.</p>	<p><i>Greenline Dezincification Resistant Ball Valve</i></p> 										
15mm	20mm	25mm																
<table border="1"> <thead> <tr> <th>10mm</th> <th>15mm</th> <th>20mm</th> <th>25mm</th> </tr> </thead> <tbody> <tr> <td>12 PCS BOX</td> <td>12 PCS BOX</td> <td>6 PCS BOX</td> <td>4 PCS BOX</td> </tr> </tbody> </table>	10mm	15mm	20mm	25mm	12 PCS BOX	12 PCS BOX	6 PCS BOX	4 PCS BOX	<p>ENDS: Screwed BSP/hose connector.</p> <p>BODY & TRIM: Nickel plated brass body, chrome plated brass ball, PTFE seats, o-ring stem seal.</p> <p>RATING: 10 bar (150 psi) CWP. 120°C max.</p> <p>APPLICATIONS: Hot and cold water, compressed air, oils, gases, fuels, non-aggressive chemicals, etc.</p>	<p><i>Bonomi Eko Ball Bib Cock</i></p> 								
10mm	15mm	20mm	25mm															
12 PCS BOX	12 PCS BOX	6 PCS BOX	4 PCS BOX															
<table border="1"> <thead> <tr> <th>15mm</th> <th>20mm</th> </tr> </thead> <tbody> <tr> <td>20 PCS BOX</td> <td>12 PCS BOX</td> </tr> </tbody> </table>	15mm	20mm	20 PCS BOX	12 PCS BOX	<p>ENDS: BSP M/F (male end for copper pipe).</p> <p>BODY & TRIM: Nickel plated brass body, full bore chrome plated brass ball, PTFE seats.</p> <p>RATING: CWP - 45 bar. Max. temp. 150°C.</p> <p>APPLICATIONS: Hot and cold water.</p>	<p><i>Bonomi Topic Ball Valve Male End for Copper Tube</i></p> 												
15mm	20mm																	
20 PCS BOX	12 PCS BOX																	
<table border="1"> <thead> <tr> <th>15mm</th> <th>20mm</th> <th>50mm</th> </tr> </thead> <tbody> <tr> <td>12 PCS BOX</td> <td>10 PCS BOX</td> <td>2 PCS BOX</td> </tr> </tbody> </table>	15mm	20mm	50mm	12 PCS BOX	10 PCS BOX	2 PCS BOX	<p>ENDS: BSP F/F.</p> <p>BODY & TRIM: Nickel plated brass body, chrome plated brass ball, PTFE seats.</p> <p>RATING: CWP - 27 bar. Max temp 120°C.</p> <p>APPLICATIONS: Irrigation.</p>	<p><i>T & S Ball Valve</i></p> 										
15mm	20mm	50mm																
12 PCS BOX	10 PCS BOX	2 PCS BOX																

NEW PLYMOUTH STEEL SUPPLIES LTD

BALL VALVES

8mm	10mm	15mm	20mm
25mm	32mm	40mm	50mm
65mm	80mm		
Code: ABVSS		Screwed Ends	


ENDS:
Screwed BSP taper.

BODY & TRIM:
3-piece 316 stainless steel body, ball and stem. Full bore. Glass reinforced PTFE seats and seals.

RATING:
69 bar CWP (1,000 psi). Temps up to 230°C.

APPLICATIONS:
General industrial use in a corrosive environment or with corrosive fluids, where serviceability is required.

Asmuss A-Ball Stainless Steel Ball Valve



8mm	10mm	15mm	20mm
25mm	32mm	40mm	50mm
65mm	80mm		
Code: VMBVSS		Screwed Ends	


ENDS:
Screwed BSP taper.

BODY & TRIM:
3-piece 316 stainless steel body, ball and stem. PTFE seats and seals.

RATING:
69 bar CWP (1,000 psi). Temps up to 210°C.

APPLICATIONS:
General industrial use in a corrosive environment or with corrosive fluids, where serviceability is required.

VM Stainless Steel Ball Valve



15mm	20mm	25mm	32mm
40mm	50mm		
Code: ABVSSST		Screwed Ends	


ENDS:
Screwed BSP taper.

BODY & TRIM:
3-piece 316 stainless steel body, ball and stem. Full bore. Graphite reinforced PTFE seats and seals.

RATING:
69 bar CWP (1,000 psi). Temps up to 230°C.

APPLICATIONS:
Steam service.

Asmuss A-Ball Stainless Steel Ball Valve with Steam Seats



8mm	10mm	15mm	20mm
25mm	32mm	40mm	50mm
65mm	80mm		
Code: VMBVSS2			


ENDS:
Screwed BSP.

BODY & TRIM:
2-piece 316 S/S body, S/S ball and stem, PTFE seats and seals, full bore.

RATING:
CWP to 1,000 psi. Temps up to 200°C.

APPLICATIONS:
General industrial use, for corrosive fluids.

VM Stainless Steel Ball Valve



15mm	20mm	25mm	32mm
40mm	50mm	EXISTING STOCK ONLY	
Code: ABVCS		Screwed Ends	
Code: ABVCSW		Socket Weld Ends	


ENDS:
Screwed BSP and socket weld. (Sched 40)

BODY & TRIM:
3-piece carbon steel body, stainless steel ball and stem, full bore. Graphite reinforced PTFE seats/seals.




RATING:
69 bar CWP (1,000 psi). Temps up to 230°C.

APPLICATIONS:
General industrial use where serviceability is required.

Asmuss A-Ball Carbon Steel Ball Valve




NEW PLYMOUTH STEEL SUPPLIES LTD

BALL VALVES																		
<table border="1"> <tr> <th>25mm</th> <th>40mm</th> <th>50mm</th> <th>65mm</th> </tr> <tr> <td> </td> <td> </td> <td> </td> <td> </td> </tr> <tr> <th>80mm</th> <th>100mm</th> <th>150mm</th> <td> </td> </tr> <tr> <td> </td> <td> </td> <td> </td> <td> </td> </tr> </table> <p>Code: ABVCS150</p>	25mm	40mm	50mm	65mm					80mm	100mm	150mm						<p>ENDS: Flanged ANSI 150. BODY & TRIM: 2-piece cast steel body, S/S ball, RPTFE seats, full bore. RATING: ANSI 150. APPLICATIONS: General industry, hydrocarbon and mineral processes.</p>	<p><i>Asmuss A-Ball CS Ball Valve M215</i></p> 
25mm	40mm	50mm	65mm															
80mm	100mm	150mm																
<table border="1"> <tr> <th>15mm</th> <th>20mm</th> <th>25mm</th> <th>40mm</th> </tr> <tr> <td> </td> <td> </td> <td> </td> <td> </td> </tr> <tr> <th>50mm</th> <th>65mm</th> <th>80mm</th> <th>100mm</th> </tr> <tr> <td> </td> <td> </td> <td> </td> <td> </td> </tr> </table> <p>Code: ABVSS150</p>	15mm	20mm	25mm	40mm					50mm	65mm	80mm	100mm					<p>ENDS: Flanged ANSI 150. BODY & TRIM: 2-piece ASTM CF8M body and ball, RPTFE seats, full bore. RATING: ANSI 150. APPLICATIONS: General industry, hydrocarbon and mineral processes.</p>	<p><i>Asmuss A-Ball Stainless Steel Ball Valve M215</i></p> 
15mm	20mm	25mm	40mm															
50mm	65mm	80mm	100mm															
<table border="1"> <tr> <th>10mm</th> <th>15mm</th> <th>20mm</th> <th>25mm</th> </tr> <tr> <td> </td> <td> </td> <td> </td> <td> </td> </tr> <tr> <th>32mm</th> <th>40mm</th> <th>50mm</th> <td> </td> </tr> <tr> <td> </td> <td> </td> <td> </td> <td> </td> </tr> </table> <p>Code: ABVSSSWL Socket Weld Ends (SCH40)</p>	10mm	15mm	20mm	25mm					32mm	40mm	50mm						<p>ENDS: Socket weld to suit Sched 40. BODY & TRIM: Ends 316L. Body, ball and stem 316 S/S. Full bore. Glass reinforced PTFE seats and seals. RATING: 69 bar CPW (1,000 psi). Temperatures up to 230°C. APPLICATIONS: General industrial use in a corrosive environment or with corrosive fluids, where serviceability is required.</p>	<p><i>Asmuss A-Ball Stainless Steel Socket Weld Ball Valve 316L Ends</i></p> 
10mm	15mm	20mm	25mm															
32mm	40mm	50mm																
<table border="1"> <tr> <th>15mm</th> <th>20mm</th> <th>25mm</th> <th>40mm</th> </tr> <tr> <td> </td> <td> </td> <td> </td> <td> </td> </tr> <tr> <th>50mm</th> <td> </td> <td> </td> <td> </td> </tr> <tr> <td> </td> <td> </td> <td> </td> <td> </td> </tr> </table> <p>Code: ABVSSSTU Socket Weld Ends to suit S/S OD Tube</p>	15mm	20mm	25mm	40mm					50mm								<p>ENDS: Socket weld to suit S/S OD Tube. BODY & TRIM: Ends 316L. Body, ball and stem 316 S/S. Full bore. Glass reinforced PTFE seats and seals. RATING: 69 bar CPW (1,000 psi). Temperatures up to 230°C. APPLICATIONS: General industrial use in a corrosive/food environment or with corrosive fluids, where serviceability is required.</p>	<p><i>Asmuss A-Ball Stainless Steel Socket Weld Ball Valve for S/S OD Tube</i></p> 
15mm	20mm	25mm	40mm															
50mm																		
<table border="1"> <tr> <th>15mm</th> <th>20mm</th> <th>25mm</th> <th>32mm</th> </tr> <tr> <td> </td> <td> </td> <td> </td> <td> </td> </tr> <tr> <th>40mm</th> <th>50mm</th> <td> </td> <td> </td> </tr> <tr> <td> </td> <td> </td> <td> </td> <td> </td> </tr> </table> <p>Code: VMBVISO</p>	15mm	20mm	25mm	32mm					40mm	50mm							<p>ENDS: Screwed BSP taper. BODY & TRIM: 3-piece 316 stainless steel body, ball and stem. PTFE seats and seals. RATING: 69 bar CPW (1,000 psi). Temps up to 230°C. APPLICATIONS: General industrial use in a corrosive/food environment or with corrosive fluids, where serviceability is required.</p>	<p><i>VM Stainless Steel Ball Valve ISO top plate</i></p> 
15mm	20mm	25mm	32mm															
40mm	50mm																	

NEW PLYMOUTH STEEL SUPPLIES LTD

BALL VALVES

<table border="1"> <tr> <th>50mm</th> <th>80mm</th> <th>100mm</th> </tr> <tr> <td> </td> <td> </td> <td> </td> </tr> </table>	50mm	80mm	100mm				<p>ENDS: Flanged ANSI 150.</p> <p>BODY & TRIM: C/S body, S/S trim, PTFE seats, lever operated, manufactured to BS5351.</p> <p>RATING: ANSI Class 150, firesafe to API607, BS6755.</p> <p>APPLICATIONS: General industry, fuels, gases, oil, chemicals, etc.</p>	<p><i>Neles Jamesbury Series 6150 Ball Valve</i></p> 										
50mm	80mm	100mm																
<table border="1"> <tr> <th>8mm</th> <th>10mm</th> <th>15mm</th> <th>20mm</th> </tr> <tr> <td> </td> <td> </td> <td> </td> <td> </td> </tr> <tr> <th>25mm</th> <th>32mm</th> <th>40mm</th> <td> </td> </tr> <tr> <td> </td> <td> </td> <td> </td> <td> </td> </tr> </table>	8mm	10mm	15mm	20mm					25mm	32mm	40mm						<p>ENDS: Screwed BSP parallel.</p> <p>BODY & TRIM: Zinc plated steel body, chrome plated steel ball, Delrin seats, NBR seals.</p> <p>RATING: Up to 15mm 500 BAR. 20mm and up. 320 BAR. Temp. -20°C to 100°C.</p> <p>APPLICATIONS: High pressure liquids and gases.</p>	<p><i>Cioca High Pressure Ball Valve</i></p> 
8mm	10mm	15mm	20mm															
25mm	32mm	40mm																
<table border="1"> <tr> <th>15mm</th> <th>20mm</th> <th>25mm</th> </tr> <tr> <td> </td> <td> </td> <td> </td> </tr> </table>	15mm	20mm	25mm				<p>ENDS: Screwed BSP parallel.</p> <p>BODY & TRIM: Zinc plated steel body, chrome plated steel ball, Delrin seats, NBR seals.</p> <p>RATING: Up to 15mm 500 BAR. 20mm and up. 320 BAR. Temp. -20°C to 100°C.</p> <p>APPLICATIONS: High pressure liquids and gas service.</p>	<p><i>Cioca High Pressure 3-Way L Port Ball Valve</i></p> 										
15mm	20mm	25mm																
<table border="1"> <tr> <th>15mm</th> <th>20mm</th> <th>25mm</th> <th>32mm</th> </tr> <tr> <td> </td> <td> </td> <td> </td> <td> </td> </tr> <tr> <th>40mm</th> <th>50mm</th> <td> </td> <td> </td> </tr> <tr> <td> </td> <td> </td> <td> </td> <td> </td> </tr> </table>	15mm	20mm	25mm	32mm					40mm	50mm							<p>ENDS: Screwed BSP.</p> <p>BODY & TRIM: 316 S/S body, ball and stem. Reinforced PTFE seats.</p> <p>RATING: 55 Bar CWP (800 PSI). Temperatures up to 230°C.</p> <p>APPLICATIONS: General industry and chemical service where diverting to on or two ports is required.</p>	<p><i>Asmuss A-Ball 3 Way L & T Port 316 S/S Ball Valves</i></p> 
15mm	20mm	25mm	32mm															
40mm	50mm																	
<table border="1"> <tr> <td>Code: ABVSSL</td> <td>L PORT</td> </tr> <tr> <td>Code: ABVSST</td> <td>T PORT</td> </tr> </table>	Code: ABVSSL	L PORT	Code: ABVSST	T PORT														
Code: ABVSSL	L PORT																	
Code: ABVSST	T PORT																	